


# V-5300, V-2500 and V-2300

## Portable Visual Presenters

### KEY FEATURES: Model V-5300


- 18X Power Optical Zoom + 4X Digital Zoom = up to 72X magnification.
- Precision AutoFocus and Power Manual Focus adjustment.
- Auto Iris with Manual Adjustment for optimum brightness.
- Highly sensitive camera & lens system: responsive down to 3 Lux.
- Room light is often sufficient for superb results with opaque material.
- Swing-Down Top Lighting enhances the reproduction of 3D objects.
- Built-In Backlight in base illuminates transparencies and slides.
- Folds-down in seconds to become truly portable. Built-in handle.



### KEY FEATURES: Model V-2500

If subjects will be only flat opaque material, the V-2500 is an excellent choice. It offers the same camera and lens as the V-5300, without the cost of top and base lights. Plus:

- Manual override of Auto White Balance for Indoor and Outdoor settings.
- Both Normal 4:3 and Widescreen 16:9 aspect ratios.
- The picture can be Reversed (right/left).



### KEY FEATURES: Model V-2300

The V-2300 combines a simpler camera and lens, for a lower cost system.

- Even higher light sensitivity: responsive down to 1 Lux.

### SPECIFICATIONS:

	<u>V-5300</u>	<u>V-2500</u>	<u>V-2300</u>
Optical Zoom Magnification	18X	18X	12X
Digital Zoom Magnification	4X	4X	No
Maximum Stage Area (HxW)	9.2 x 12.3 in. (232 x 312 mm)	8.9 x 12.0 in (225 x 305 mm)	9.3 x 12.6 in. (236 x 320 mm)
Minimum Stage Area (HxW)	0.59 x 0.79 in. (15 x 20 mm)	0.59 x 0.79 in. (15 x 20 mm)	0.83 x 1.10 in. (21 x 28 mm)
Sensitivity	as low as 3 Lux	as low as 3 Lux	as low as 1 Lux
Lens Speed / Focal Length	f:1.4-3.0 / (4.1-73.8 mm)	f:1.4-3.0 / (4.1-73.8 mm)	f:1.8-2.7 / (5.4-64.8 mm)
Focus	Auto. One-Touch. Motor-Driven	Auto. One-Touch. Motor-Driven	Auto. One-Touch. Motor-Driven
Iris	Auto, with Manual Adjustment	Auto, with Manual Adjustment	Auto, with Manual Adjustment
Camera Type	1/4 inch CCD	1/4 inch CCD	1/3 inch CCD
Total Pixels	415,544	415,544	415,544
Active Pixels	390,393	390,393	390,393
Synchronization	Internal	Internal	Internal
Horizontal Resolution	470 TV Lines	470 TV Lines	460 TV Lines
Signal/Noise Ratio	more than 50 dB	more than 50 dB	more than 48 dB
White Balance	Auto	Auto / Indoor / Outdoor	Auto / Indoor / Outdoor
White/Black Mode	Selectable	Selectable	No
Detail Image Mode	Soft / Normal / Sharp	No	No
Negative-Positive Inversion	Yes	Yes	No
Freeze Function	Yes	Yes	No
Brightness Adjustment	Yes	Yes	Yes
Color Adjustment	Yes	Yes	Yes
Aspect Ratio (W:H)	4:3	4:3 / 16:9 (selectable)	4:3
Left/Right Reversal	No	Yes	No
Top Lighting (Arms)	Fluorescent x 2	No	No
Back Lighting (Base)	Yes	No	No
Video Output	C-Video (RCA) X 1; S-Video X 1	C-Video (RCA) X 2; S-Video X 1	C-Video (RCA) X 2; S-Video X 1
Microphone Input	1/4 inch Phone Jack x 1	No	No
Audio Output	RCA x 1	No	No
IR Remote Control	15 Keys	15 Keys	9 Keys
Net Weight	12.8 lb (5.8 kg)	3.3 lb (1.5 kg)	3.3 lb (1.5 kg)
Dimensions: Open (HxWxD)	20.5x15.5x17.9 in (521x394x454mm)	18.3x13.8x10.9 in (463x350x275 mm)	18.3x13.8x10.9 in (463x350x275 mm)
Dimensions: Closed (HxWxD)	4.2x15.5x17.9 in (106x394x454 mm)	3.9x11.5x15.75 in (98x290x400 mm)	3.9x11.5x15.75 in (98x290x400 mm)
Power Supply	Built-In: Detachable Power Cord	AC Adapter (DC 6.5V)	AC Adapter (DC 6.5V)
Power Requirements	100-120 VAC, 50/60 HZ	100-120 VAC, 50/60 HZ	100-120 VAC, 50/60 HZ
Power Consumption	16 W	3.5 W	3 W
Rotatable Head	Yes	Yes	Yes
Removable Close-up Lens	Yes	Yes	Yes
Warranty	1 Year: Parts and Labor	1 Year: Parts and Labor	1 Year: Parts and Labor

Specifications subject to change without notice. ©2001 Eiki International, Inc. Printed in the USA. November 21, 2001

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2130 Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com  
 In Canada, 310 First St.- Unit 2, P.O. Box 156, Midland, ON L4R 4K8 Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

**Fax-on-Demand: (Toll Free) 877-345-4329 • Visit our World Wide Web site: <http://www.eiki.com>**